

Flexible dual Medium wall tubing, halogen free with 3:1 shrink ratio. Quick and easy to install with strong adhesive for excellent insulation and complete waterproof.

Characteristics

- Operating Temperature:
-55°C ~ 120°C
- Min. Shrink Temperature: 90°C
- Shrink Ratio: 3:1
- Dielectric Strength: 21 kV/mm
- Standard Colour(s): Black

DUAL WALL POLYOLEFIN



Application Fields

Encapsulating and anti-corrosion protection of metal pipes. Insulation for communication equipment and cables. Alternative to taping in medium voltage applications.

Table of Standard Sizes and Packaging

| SCM2 Size | Inside Diameter (mm) | | | Wall Thickness (mm) Recovered(nom) | Quantity per Bag / Box (m) |
|--------------|----------------------|---|------|--|-------------------------------|
| | Expanded (min.) | Recovered (max.) (outer layer only) (nom.) | | | |
| 04 | 10.2 | 3.80 | 2.30 | 1.50 | 12/120 |
| 07 | 19.0 | 5.60 | 4.10 | 2.00 | 12/120 |
| 11 | 28.0 | 9.5 | 6.5 | 2.00 | 12/60 |
| 13 | 33.0 | 10.2 | 7.8 | 2.00 | 12/60 |
| 15 | 38.1 | 12.7 | 10.3 | 2.30 | 12/48 |
| 17 | 44.0 | 14.0 | 11.6 | 2.30 | 12/48 |
| 20 | 52.1 | 18.2 | 15.8 | 2.30 | 6/30 |
| 27 | 70.0 | 25.5 | 23.1 | 2.30 | 6/24 |
| 35 | 90.0 | 30.0 | 27.6 | 2.50 | 3.6/18 |
| 50 | 125.0 | 40.0 | 37.6 | 2.50 | 2.4/24 |

