

Flexible polyolefin halogen free tubing with inner liner of hot melt adhesive. High shrink ratio eases installation on transitions with large diameter gaps. Transparent colour enables visual inspection of substrate.

### Characteristics

- Operating Temperature:  
-55°C ~ 105°C
- Min. Shrink Temperature: 110°C  
Shrinking start at 60°C
- Shrink Ratio: 3:1, 4:1
- Dielectric Strength: 30 kV/mm
- Standard Colour(s): Transparent

### DUAL WALL POLYOLEFIN



### Application Fields

Waterproof sealing and encapsulation of connectors, harnesses, ultra-sonic splices and water sensitive electrical components. Especially where visual inspection is required.

Table of Standard Sizes and Packaging

W5C Type/Size (mm)	Inside Diameter (mm)		Wall Thickness (mm)		Quantity per Bag / Box (m)
	Expanded (min.)	Recovered (max.)	Recovered nom. (inner liner)		
3/1	3.00	1.00	0.96(0.35)		60/600
4.5/1.5	4.50	1.50	1.06 (0.60)		60/300
6/2	6.0	2.00	1.19 (0.65)		60/300
9/3	9.0	3.00	1.27 (0.65)		30/150
12/4	12.0	4.00	1.40 (0.75)		30/150
19/6	19.0	6.0	1.80 (0.70)		18/90
24/8	24.0	8.0	2.50 (1.00)		18/90
40/13	40.0	13.0	2.50 (1.00)		6/24
W5C(4X)					
4/1	4.00	1.00	1.00 (0.50)		60/300
8/2	8.0	2.00	1.20 (0.50)		30/150
12/3	12.0	3.00	1.40 (0.50)		30/150
16/4	16.0	4.00	1.80 (0.60)		30/150
24/6	24.0	6.0	2.25 (0.80)		18/90
32/8	32.0	8.0	2.55 (1.00)		6/24